

MB ASUS AMD AM4 PRIME A520M-K

Šifra: 884

Kategorija proizvoda: AMD Matične ploče

Proizvođač: ASUS

Cena: **7.409,00** rsd.



CPU

Build in AMD AM4 Socket Processors *

* Refer to www.asus.com for CPU support list

Chipset

AMD A520

Graphic

1 x D-Sub

1 x HDMI 2.1(4K@60HZ)

Storage

Total supports 1 x M.2 slot(s) and 4 x SATA 6Gb/s ports

3rd Gen AMD Ryzen™ and 3rd Gen AMD Ryzen™ with Radeon™ Graphics Processors :

1 x M.2 Socket 3, with M Key, Type 2242/2260/2280 (PCIe 3.0 x4 and SATA modes) storage devices support

AMD A520 Chipset :

4 x SATA 6Gb/s port(s),

Support Raid 0, 1, 10

Audio

Realtek ALC887 7.1 Surround Sound High Definition Audio CODEC *

- Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback

Audio Feature :

- Audio Shielding

- Dedicated audio PCB layers

* Choose the chassis with HD audio module in front panel to support 8-channel audio output.

Software Features

ASUS Exclusive Software

Armoury Crate

AI Suite 3

- Performance and Power Saving Utility

TurboV EVO

EPU

Digi+ VRM

Fan Xpert

- EZ update

ASUS CPU-Z

AI Charger

DAEMON Tools

Norton Anti-virus software (Free Trial for 60 days)

Memor

2 x DIM

4600(C

MHz) H

Expans

3rd Ge

With R

* Refer

AMD A

* The n

proces

LAN

Realtek

ASUS L

USB Po

Rear U

4 x US

2 x US

Front

2 x US

4 x US

WinRAR
UEFI BIOS
ASUS EZ DIY
- ASUS CrashFree BIOS 3
- ASUS EZ Flash 3
- ASUS UEFI BIOS EZ Mode

ASUS Special Features
ASUS 5X PROTECTION III
- ASUS DIGI+ VRM
- ASUS LANGuard
- ASUS Overvoltage Protection
- ASUS SafeSlot Core
- ASUS Stainless-Steel Back I/O
ASUS Q-Design
- ASUS Q-DIMM
- ASUS Q-Slot
ASUS Thermal Solution
- Aluminum heatsink design
Internal I/O Ports
1 x CPU Fan connector(s)
1 x Chassis Fan connector(s)
1 x USB 3.2 Gen 1(up to 5Gbps) connector(s) support(s)
additional 2 USB 3.2 Gen 1 port(s)
2 x USB 2.0 connector(s) support(s) additional 4 USB
2.0 port(s)
1 x M.2 Socket 3 with M key, type 2242/2260/2280
storage devices support (SATA & PCIE 3.0 x 4 mode)
1 x SPI TPM header
4 x SATA 6Gb/s connector(s)
1 x S/PDIF out header(s)
1 x 24-pin EATX Power connector(s)
1 x 8-pin EATX 12V Power connectors
1 x Front panel audio connector(s) (AAFP)
1 x Clear CMOS jumper(s)
1 x System panel connector
1 x COM port header
1 x Speaker connector
BIOS
256 Mb Flash ROM, UEFI AMI BIOS

Operating System
Windows® 10 64-bit

Back I/O
1 x PS/2
1 x D-Sub
1 x HD
1 x LAN
4 x USB
2 x USB
3 x Audio

Accessories
User's Manual
I/O Shield
2 x SATA
1 x Super
1 x M.2

Management
WOL by

Form Factor
mATX
8.9 inch